



Product Data Sheet

Eruption S

January, 2025

Type of flooring	EN ISO 26986	Expanded (cushioned) polyvinyl chloride floor covering
Class of use	ISO 10874 (EN 685)	
CE certification	EN 14041:2004/AC:2006	2701-0106-DoP-2024-01

TECHNICAL CHARACTERISTICS AND PERFORMANCES

	ISO 24346 (EN 428) Total thickness	2,70 mm		ISO 24341 (EN 426) Roll lenght Roll width	38m (15-38) 23m (15-33) 3; 4m
	ISO 24340 (EN 429) Wear layer thickness	0,15 mm		ISO 24343-1 (EN 433) Residual indentation	≤ 0,35 mm
	ISO 23997 (EN 430) Weight per m ²	1,46 kg/m ²		Underfloor heating Suitable provided that the surface of the subfloor does not exceed 27°C	
	ISO 105 B02 Method 3 Light fastness	≥ 6		EN 13893 Slip resistance	
	ISO 23999 (EN 434) Dimensional stability	Requirement by standard: < 0,4 % Tarkett result: ≤ 0,011 %		EN 12524 Thermal resistance	0,038 - 0,044m ² /kW
	EN 13501-1 Fire classification	Bfl-s1			

Wear layer binder content ISO 11638 Type I



2701-0106-DoP-2024-01



This product is 100% recyclable

